



HTL RANGE

ENGINEERED TO BOOST
YOUR PERFORMANCE

Haulotte 
GROUP

More than lifting



COMPACT

HTL3210 - HTL3510 - HTL4010



PERFORMANCES

	HTL 3210	HTL 3510	HTL 4010
Maximum lift capacity	3200 kg	3500 kg	4000 kg
Lift capacity to full height	2500 kg	2000 kg	2500 kg
Lift capacity at full reach	850 kg	500 kg	1200 kg
Maximum fork height	10 m	10 m	10 m
Reach at maximum fork height	2.2 m	2.2 m	2.2 m
Maximum forward reach	7.2 m	7.2 m	7.2 m
Speed in travelling mode	25 km/h	25 km/h	25 km/h
Turning radius (outside wheels)	3.7 m	3.7 m	3.7 m
Weight with forks	7950 kg	8610 kg	8740 kg
Tyres type	405/70 - 20	405/70 - 24	405/70 - 24
Engine model	Kohler / Perkins	Kohler / Perkins	Kohler / Perkins
Outriggers	Yes	Yes	Yes
Tilt corrector	No	Yes	No

DIMENSIONS

	HTL 3210	HTL 3510	HTL 4010
A- Length	4.96 m	4.96 m	4.96 m
B- Width	2.26 m	2.26 m	2.26 m
C- Height	2.38 m	2.42 m	2.42 m
D- Wheelbase	2.78 m	2.78 m	2.78 m
E- Ground clearance	42 cm	42 cm	42 cm
F- Track width	1.88 m	1.88 m	1.88 m
G- Cab width	0.96 m	0.96 m	0.96 m
H- Overall width - stabilizers down	2.26 m	-	2.26 m





HIGH LIFT

HTL3614 - HTL3617 - HTL4014 - HTL4017



PERFORMANCES

	HTL 3614	HTL 3617	HTL 4014	HTL 4017
Maximum lift capacity	3600 kg	3600 kg	4000 kg	4000 kg
Lift capacity to full height	3000 kg	2500 kg	3000 kg	2500 kg
Lift capacity at full reach	800 kg	500 kg	1000 kg	700 kg
Maximum fork height	13.6 m	16.7 m	13.6 m	16.7 m
Reach at maximum fork height	1.5 m	2.4 m	1.5 m	2.4 m
Maximum forward reach	9.8 m	12.85 m	9.8 m	12.85 m
Speed in travelling mode	30 km/h	30 km/h	30 km/h	30 km/h
Turning radius (outside wheels)	4.5 m	4.5 m	4.5 m	4.5 m
Weight with forks	10340 kg	11590 kg	10710 kg	12000 kg
Tyres type	405/70 - 24	405/70 - 24	400/80-24	400/80-24
Engine model	Kohler / Perkins	Kohler / Perkins	Kohler / Perkins	Kohler / Perkins
Outriggers	Yes	Yes	Yes	Yes
Tilt corrector	STD	STD	STD	STD

DIMENSIONS

	HTL 3614	HTL 3617	HTL 4014	HTL 4017
A- Length	6.43 m	6.56 m	6.46 m	6.65 m
B- Width	2.43 m	2.43 m	2.43 m	2.43 m
C- Height	2.6 m	2.6 m	2.6 m	2.6 m
D- Wheelbase	2.89 m	2.89 m	2.89 m	2.89 m
E- Ground clearance	50 cm	50 cm	50 cm	50 cm
F- Track width	2 m	2 m	1.93 m	1.93 m
G- Cab width	0.96 m	0.96 m	0.96 m	0.96 m
H- Overall width - stabilizers down	3.34 m	3.34 m	3.34 m	3.34 m





HEAVY LOAD CAPACITY

HTL5210 - HTL6508 - HTL7210



PERFORMANCES

	HTL 5210	HTL 6508	HTL 7210
Maximum lift capacity	5200 kg	6500 kg	7200 kg
Lift capacity to full height	5200 kg	4200 kg	3800 kg
Lift capacity at full reach	3500 kg	2000 kg	2000 kg
Maximum fork height	10 m	7.7 m	9.5 m
Reach at maximum fork height	0.3 m	0.6 m	0.7 m
Maximum forward reach	5.7 m	4.2 m	5.4 m
Speed in travelling mode	30 km/h	30 km/h	30 km/h
Turning radius (outside wheels)	4,5	4.4 m	4.4 m
Weight with forks	10810 kg	11260 kg	12200 kg
Tyres type	400/80-24	18x22.5"	18x22.5"
Engine model	Perkins (TIER IV / TIER III)	FPT (TIER IV i)	FPT (TIER III)
Outriggers	Yes	No	No
Tilt corrector	Yes	No	No

DIMENSIONS

	HTL 5210	HTL 6508	HTL 7210
A- Length	6.28 m	5.05 m	5.91 m
B- Width	2.43 m	2.39 m	2.38 m
C- Height	2.6 m	2.5 m	2.49 m
D- Wheelbase	2.89 m	2.8 m	2.95 m
E- Ground clearance	50 cm	40 cm	44 cm
F- Track width	2 m	1.92 m	1.92 m
G- Cab width	0.96 m	0.94 m	0.94 m
H- Overall width - stabilizers down	3.34 m	-	-

